

## VATROOTPORNA ZAŠTITA CRIJEVA

Standards: UL 1441 VW -I-EN 45545-1 EN 45545-2+A1

TEMPERATURE RANGE: -40°C do +260°C

Fire resistance: self-extinguishes



Zaštitna navlaka od stakloplastike prekrivena crvenim silikonom za visoku izolaciju i temperaturnu otpornost hidrauličnih i industrijskih fleksibilnih crijeva za produljenje vijeka trajanja.



Fiberglass sleeving covered with red silicon for high insulation and temperatures resistance of hydraulic and industrial flexible hoses which extends the working life.



Защитный рукав из стекловолокна, покрытого красным силиконом для высокой изоляции и термостойкости гидравлических и промышленных гибких рукавов для продления срока службы.

Oleum Flex Code	Part Description	Hose OD	Fiberglass diam. micron	Silicon wall	Coil Length
		mm		thickness mm	met
15087	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 15 MM RED	15	9	1	20
15088	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 20 MM RED	20	9	1	20
15089	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 25 MM RED	25	9	1	20
15090	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 30 MM RED	30	9	1	20
15091	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 35 MM RED	35	9	1	20
15092	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 41 MM RED	41	9	1	20
15093	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 45 MM RED	45	9	1	20
15094	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 52 MM RED	52	9	1	20
15095	FIBERGLASS SLEEVING FOR HOSE OUTSIDE DIMENSION 65 MM RED	65	9	1	20